

# SMT LEAD FORM & TRIM

# Solutions

BENCH AIR PRESSES...

## Quality, Performance and Versatility



Fancort's quiet, smooth action bench air presses are designed with a high degree of functionality and versatility for light assembly work up to 4.0 tons. The deep throat, large bed area and stable base make these presses the most user friendly on the market. They have clean and simple packaging with a shroud to enclose the cylinder, tubing and controls. The presses come standard with all controls in place including a counter, and even have provisions for die mounting. **Shipped "ready-to-run!"**

- ◆ 13 1/4" x 16" bed area with ram 7.125" from front of die plate with 1.5" x 1" die shank collar; 22" wide die plate available
- ◆ Two-hand OSHA approved safety system
- ◆ Rigid 'C' frame with 1" thick aluminum side walls to prevent flexing and allow robotic loading
- ◆ Tough nitro blue enamel finish and hard coat aluminum die plate with three sets of tapped holes for die mounting
- ◆ 4" stroke, 7.25" shut height
- ◆ Double acting 5" cylinder (1 ton), cushioned cap; other models to 4 tons
- ◆ Speed control, filter / regulator, dual palm controls, counter and front mounted air gauge
- ◆ Measures: 21" x 13.5" x 28" (5000 only)
- ◆ Optional non-rotating rams, stroke lengths, and timers available

### Description—complete press with all controls:

- with 5" cylinder, approximately 1 ton, 16" inside width
- with 5" cylinder, approximately 1 ton, 22" inside width
- with 6" cylinder, 1.4 ton, 16" inside width
- and tandem 6" cylinder, 2.8 ton, 16" inside width
- and tandem 6" cylinder & accumulator, approximately 4 ton, 16" inside width
- 4" air stroke over 1/2" hydraulic, approximately 4 ton, 16" inside width

Part #	Cycle Time	Price
5000L	2-5 sec	\$3800
5000L-22	2-5 sec	\$6000
5000L-6	2-5 sec	\$4200
5000L-8	6-7 sec	\$5565
5000L-10	2-45 sec	\$6850
6000/SP	2-4 sec	\$11,505



fancort industries, inc.

31 Fairfield Place  
West Caldwell, NJ 07006 USA  
973-575-0610 FAX 973-575-9234