

# Assembly *Solutions*

## Smart Press....

Quality and Performance and Value

For small work and small budgets

Fancort's offers economical, programmable, electrically operated servo press technology for critical assembly applications that can't be done with air or hydraulic presses.

### Key Features:

- Program force from 2.2 lbs to 120 lbs; other models to 1100 lbs
- Small footprint and adjustable column w/11" of throat adjustment
- 8" x 6" base w/keyway and two bolts for tool mounting
- Two-hand non-contact safety controls
- 4" stroke,; optional strokes available from 2" to 12"
- Positioning accuracy of +/- .004" (.01mm)
- Control force to a tolerance of +/- 10% of target point
- Program with teaching pendant P/N CTA-23 EN-SET
- User friendly software for programming from PC; includes data output for SPC; software also allows the use to run the press from a PC
- Store up to 16 programs
- Closed loop servo motor and servo amplifier
- Measures 9" x 10" x 16"
- Weighs 40 lbs
- Model BP-500E-60



BP-500E-60-4 Shown with 4" Stroke

| Model         | Pressure |
|---------------|----------|
| BP-500-60-X   | 120 LBS  |
| 5000LE-500-X  | 1100 LBS |
| 5000LE-1000-X | 2200 LBS |

<sup>x</sup> Specifies stroke length